

# CORTEGA®/CORTEGA Second Look®

Square Lay-in & Tegular  
medium texture



Cortega Angled Tegular with Prelude® 15/16" suspension system (Pg. 259)



Cortega Second Look II with Suprafine® 9/16" suspension system (Pg. 266)

## KEY SELECTION ATTRIBUTES

- Economical
- Non-directional visual reduces installation time and scrap (excludes Second Look items)
- Geometric Scored Visuals (Second Look items)

## TYPICAL APPLICATIONS

- Many types of commercial interiors
- Discount stores
- Utility Rooms

## COLOR



White (WH) Tech Black (BL)  
Item 769



Colored ceilings are dye-lotted and should be segregated by dye lot. Do not mix.

## FACE VIEW



1. Cortega Second Look I – Scoring creates nominal 12" x 12" squares
2. Cortega Second Look II – Scoring creates nominal 24" x 24" squares

## DETAIL



1. Cortega Square Lay-in
2. Cortega Beveled Tegular
3. Cortega Second Look
4. Cortega Lay-in with Prelude 15/16" suspension system
5. Cortega Beveled Tegular with Suprafine 9/16" suspension system

# CORTEGA®/CORTEGA Second Look®

## Square Lay-in & Tegular

medium texture

UP TO **41%** CORTEGA **55%** CORTEGA 2<sup>nd</sup> LOOK **RECYCLED CONTENT**

**LEED®** acoustics energy daylight & views indoor air quality renewable materials recycled content waste mgmt local materials

Calculate LEED contribution at [armstrong.com/greengenie](http://armstrong.com/greengenie) \*LOCATION DEPENDENT



### VISUAL SELECTION

### PERFORMANCE


Dots represent high level of performance.

Edge Profile	Susp. Dwg. Pgs. 273-277 <a href="http://armstrong.com/catdwgs">armstrong.com/catdwgs</a>	Item No.	Dimensions (Inches)	Acoustics		Fire Rating	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability	Primary (Embodied) Energy	Recycled Content*	Recycled Program	Warranty†	
				NRC	CAC											
<b>CORTEGA Square Lay-in</b>																
	1	<b>770</b> <b>770M</b>	24 x 24 x 5/8" 600 x 600 x 15mm		UL Classified	Class A	0.82	-	Std	•	Std	•	Std	•	1	
	1	<b>824</b>	24 x 24 x 5/8"		0.55	35	Fire Guard	0.82	-	Std	•	Std	-	Std	•	1
	1	<b>769</b> ** <b>769M</b>	24 x 48 x 5/8" 600 x 1200 x 15mm		0.55	35	Class A	0.82	-	Std	•	Std	•	Std	•	1
	1	<b>823</b>	24 x 48 x 5/8"		0.55	35	Fire Guard	0.82	-	Std	•	Std	-	Std	•	1
	1	<b>747</b>	24 x 48 x 5/8"		0.55	40	Class A	0.82	-	Std	•	Std	-	Std	•	1
	1	<b>773</b> <b>773M</b>	20 x 60 x 5/8" 500 x 1500 x 15mm		0.55	35	Class A	0.82	-	Std	•	Std	•	Std	•	1
	1	<b>772</b> <b>772M</b>	24 x 60 x 5/8" 600 x 1500 x 15mm		0.55	35	Class A	0.82	-	Std	•	Std	•	Std	•	1
	1	<b>Other Sizes</b>	W: 12" - 30" / L: 18" - 72" 5/8" Thick		0.55	35	Class A	0.82	-	Std	•	Std	•	Std	•	1
<b>CORTEGA Tegular</b>																
	11	<b>704</b> <b>704M</b>	24 x 24 x 5/8" 600 x 600 x 15mm		0.55	33	Class A	0.82	-	Std	•	Std	•	Std	•	1
	11	<b>816</b>	24 x 24 x 5/8"		0.55	35	Fire Guard	0.82	-	Std	•	Std	-	Std	•	1
	11	<b>703</b>	24 x 48 x 5/8"		0.55	35	Class A	0.82	-	Std	•	Std	•	Std	•	1
	29, 44, 48, 52, 56	<b>2195</b>	24 x 24 x 5/8"		0.55	35	Class A	0.82	-	Std	•	Std	•	Std	•	1
	29, 44, 48, 52, 56	<b>Other Sizes</b>	W: 12" - 30" / L: 18" - 72" 5/8" Thick		0.55	35	Class A	0.82	-	Std	•	Std	•	Std	•	1
<b>CORTEGA Second Look I</b>																
	11	<b>2765</b>	24 x 48 x 3/4"		0.55	35	Class A	0.82	-	Std	•	Std	-	Std	•	1
<b>CORTEGA Second Look II</b>																
	11	<b>2758</b>	24 x 48 x 3/4"		0.55	40	Fire Guard	0.82	-	Std	•	Std	-	High	•	1
	11	<b>2767</b>	24 x 48 x 3/4"		0.55	35	Class A	0.82	-	Std	•	Std	-	Std	•	1
	27	<b>2776</b>	24 x 48 x 3/4"		0.55	30	Class A	0.82	-	Std	•	Std	-	Std	•	1

\*\* Add 2-letter color suffix to item number when specifying or ordering (e.g., 769 B L).

### SUSPENSION SYSTEMS

NOTE: 9/16" Cortega Second Look items are installed using Suprafine suspension systems only. Item 2195-CAC 31 on 9/16" Silhouette or Trimlok



### PHYSICAL DATA

**Material**  
Wet-formed mineral fiber

**Surface Finish**  
Factory-applied latex paint

**Fire Performance**  
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled) Fire Guard™: A fire resistive ceiling when used in applicable UL assemblies

**ASTM E1264 Classification**  
Type III, Form 2, Pattern C D

**VOC Emissions**  
Third party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title

24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol. (Excludes 769BL)

**Primary (Embodied) Energy**  
See all LCA information on our EPD's.

**High Recycled Content\***  
Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Insulation Value**  
2195, 704, 816, 703 - R Factor - 1.6 (BTU units);  
R Factor - 0.28 (Watts units)  
770, 772, 769, 773, 823, 824 - R Factor - 1.5 (BTU units); R Factor - 0.26 (Watts units)

**Application Consideration**  
Item 850 is unfinished fire protection board.

**Weight; Square Feet/Carton**  
769 - 0.61 lbs/SF; 96 SF/ctn  
704, 2195 - 0.63 lbs/SF; 64 SF/ctn  
772, 773 - 0.63 lbs/SF; 100 SF/ctn  
703 - 0.65 lbs/SF; 80 SF/ctn  
770 - 0.69 lbs/SF; 64 SF/ctn  
816 - 1.08 lbs/SF; 48 SF/ctn  
823, 824 - 1.09 lbs/SF; 64 SF/ctn  
850 - 1.11 lbs/SF; 64 SF/ctn  
2765, 2767 - 0.73 lbs/SF; 80 SF/ctn  
2758 - 1.26 lbs/SF; 64 SF/ctn  
2776 - 0.70 lbs/SF; 80 SF/ctn

**Minimum Order Quantity**  
1 carton, excludes other sizes

**Metric Items Available**  
770M, 824M, 769M, 773M, 772M, 2195M, 704M, 703M, 823M - Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.



TechLine™ / 1 877 ARMSTRONG  
[armstrong.com/commcceilings](http://armstrong.com/commcceilings)  
(search: cortega)  
BPCS-3017/3022-1113

LEED® is a registered trademark of the U.S. Green Building Council  
All other trademarks used herein are the property of AWI Licensing Company and/or its affiliates © 2013 AWI Licensing Company  
Printed in the United States of America

