

CANYON®
 Square Lay-in & Tegular
 smooth texture



CAD/Revit® drawings at:
armstrongceilings.com/cadrevit

▲ Canyon Beveled Tegular panels with Prelude XL 15/16" suspension system

Smooth-texture panel with both Sustain® and Total Acoustics® panel performance for flexible spaces.

KEY SELECTION ATTRIBUTES

- Get total noise control and floor plan versatility with Total Acoustics ceiling panels: NRC + CAC = Total Acoustics Performance
- Canyon® is part of the Sustain® portfolio, and meets the most stringent industry sustainability compliance standards today
- Mold- and mildew-resistant surface
- Smooth, white surface
- Product can be recycled through the Armstrong Ceilings Recycling Program
- Good combination of acoustical performance; NRC 0.65 and CAC 35
- 30-Year Limited System Warranty against visible sag, mold, and mildew
- 10-Year replacement panel available for items 1490, 1491, 1492, 1493, 1494, 1495



COLOR



White
 (WH)

DETAILS (Other Suspension Systems compatible. Refer to listing on next page.)



1. Canyon Square Lay-in
2. Canyon Square Lay-in with Prelude® XL 15/16" suspension system

CANYON®

Square Lay-in & Tegular
smooth texture



Declare.

GREENGUARD Gold Certified (details below)

LEED® WELL™ LBC
UP TO 44% RECYCLED CONTENT

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

Calculate sustainability with Green Genie™
armstrongceilings.com/greengenie

LOCATION DEPENDENT

VISUAL SELECTION

PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$\$

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)	UL Classified Acoustics	Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold/Mildew	Sag Resistant	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	30-Yr Warranty
CANYON® 15/16" Square Lay-in	1	1490	24 x 24 x 5/8" □	0.65	35	GOOD Class A	0.80	•	•	•	Std	Std	•	•
		1491	24 x 48 x 5/8" □	0.65	35	GOOD Class A	0.80	•	•	•	Std	Std	•	•
15/16" Beveled Tegular	15	1492	24 x 24 x 5/8" □	0.65	35	GOOD Class A	0.80	•	•	•	Std	Std	•	•
		1493	24 x 48 x 5/8" □	0.65	35	GOOD Class A	0.80	•	•	•	Std	Std	•	•
9/16" Beveled Tegular	44, 48, 29, 52, 56	1494	24 x 24 x 5/8" □	0.65	35	GOOD Class A	0.80	•	•	•	Std	Std	•	•
		1495	24 x 48 x 5/8" □	0.65	35	GOOD Class A	0.80	•	•	•	Std	Std	•	•
Made-to-Order Sizes			5/8" Thick – 15/16" Square Lay-in, 15/16" & 9/16" Beveled Tegular	N/A	N/A	N/A Class A	0.80	•	•	•	Std	Std	•	•

4-6 WEEKS order to ship

¹ Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product. **GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Mineral fiber with acoustically transparent membrane.

Surface Finish
Acoustically transparent membrane with factory-applied latex paint

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index of 25 or less. Smoke Developed Index of 50 or less (UL® labeled).

ASTM E1264 Classification
Type IV, Form 2, Pattern E; Fire Class A

Humidity/Sag Resistance
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling tiles with BioBlock® performance resist the growth of mold and mildew on the tile surface.

VOC Emissions
GREENGUARD Gold Certified
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED®, WELL Building Standard™, Living Building Challenge® (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance
CAC testing conducted on Silhouette suspension system

PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/G6
UL 2818



Insulation Value
R Factor – 1.5 (BTU units)
R Factor – 0.26 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong Suspension System. Details at armstrongceilings.com/warranty

Cleaning and Disinfecting
Cleaning and CDC-approved disinfecting options available on armstrongceilings.com/cleaning

Weight; Square Feet/Carton
0.76 lbs/SF; 64 SF/ctn

Minimum Order Quantity
1 carton, excludes made-to-order panels



MINERAL FIBER – Standard