CORTEGA® Second Look®

Tegular medium texture





△ Cortega® Second Look® II panels with Suprafine® XL® 9/16" suspension system

Medium-texture panels; Economical solution with standard acoustical absorption.

KEY SELECTION ATTRIBUTES

- Cortega® Second Look® panels are part of the Sustain® portfolio, and meet the most stringent industry sustainability compliance standards today
- Economical
- · Geometric Scored Visuals

COLOR




(WH)

FACE VIEWS



Cortega® Second Look® I panels – Scoring creates nominal 12" x 12" squares



Cortega® Second Look® II panels – Scoring creates nominal 24" x 24" squares

DETAIL



Cortega® Second Look®



CORTEGA® Second Look®

Tegular medium texture

Declare.



(details below)

xtended roducer resp.

Ħ

LOCATION DEPENDENT

| VISUAL | CEI | FCT | IUVI | |
|--------|-----|-----|------|--|
| | | | | |

PERFORMANCE SELECTION Dots represent high level of performance.

\$\$\$\$

| armstrongceilings. com/suspdwgs | Susp. Dwg. | Item No. | Dimensions (Inches) | UL Clas Acous NRC + | ssified stics | Total Acoustics¹ | Fire Performance | Light Reflect | Anti-Mold/ Mildew | Sag Resistant | Certified Low VOC Emissions | Durability | Recycled Content | Recycle Program | Warranty |
|--|---------------|----------|------------------------|---------------------------|------------------|---------------------|------------------|---------------|----------------------|------------------|--------------------------------|------------|------------------|--------------------|----------|
| CORTEGA® Second Look® I 15/16" Angled Tegular | 11 | 2765 | 24 x 48 x 3/4" | 0.55 | 35 | N/A | Class A | 0.81 | N/A | Std | ٠ | Std | Std | ٠ | 1-Yr |
| CORTEGA® Second Look® II 15/16" Angled Tegular | 11 | 2758 | 24 x 48 x 3/4" | 0.55 | 40 | N/A | Fire Guard | 0.81 | N/A | Std | ٠ | Std | ٠ | ٠ | 1-Yr |
| | | 2767 | 24 x 48 x 3/4" | 0.55 | 35 | N/A | Class A | 0.81 | N/A | Std | ۰ | Std | ٠ | • | 1-Yr |
| 9/16" Angled Tegular | 27 | 2776 | 24 x 48 x 3/4" | 0.55 | 30 | N/A | Class A | 0.81 | N/A | Std | ۰ | Std | ۰ | • | 1-Yr |

SUSPENSION SYSTEMS

15/16"



Prelude XI ® Fire Guard



PHYSICAL DATA

 ${\sf Cortega}^{\circledast}/{\sf Cortega}^{\circledast} \; {\sf Second} \; {\sf Look}^{\circledast} ; \; {\sf wet-formed} \; \\ {\sf mineral} \; {\sf fiber} \; \\$

Surface Finish Factory-applied latex paint

Factory rappines rates pain.

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface
burning characteristics. Flame Spread Index of 25 or
less. Smoke Developed Index of 50 or less (UL labeled). Fire Guard: A fire-resistive ceiling when used in applicable UL assemblies

ASTM E1264 Classification Type III, Form 2, Pattern C D K

Humidity/Sag Resistance Standard performance celling panels are recommended where the building is enclosed and the HVAC is continuously functioning.

VOC Emissions PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL 2818 VOC Emissions (PB suffix items only) FOR UN CHEMICAL (PB

Primary (Embodied) Energy See all LCA information on our EPDs.



High Recycled Content Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value 2765, 2758, 2767, 2776 – R Factor – 1.5 (BTU units); R Factor – 0.28 (Watts units)

Weight; Square Feet/Carton 2765, 2767 - 0.73 lbs/SF; 80 SF/ctn 2758 - 1.26 lbs/SF; 64 SF/ctn 2776 - 0.70 lbs/SF; 80 SF/ctn

Minimum Order Quantity



Red Numbers are Fire Guard items.

1 Total Acoustics® ceiling panels have an ideal combination of sound absorption and sound blocking in one product.